



# Technical Description for Thor-8-PCI and Thor-8-PCIe

Doc. No. 1111-1-HAA-1019-1

Rev. 1.3

September 22, 2012

## Copyright

Copyright (C) Odin TeleSystems Inc., 1999-2012. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written consent of Odin TeleSystems Inc., P. O. Box 59686, Dallas, Texas, 75229, U. S. A.

## Trademarks

Odin TeleSystems, the Odin Logo, OTX, and Thor-8-PCI and Thor-8-PCIe are trademarks of Odin TeleSystems Inc., which may be registered in some jurisdictions. Other trademarks are the property of their respective companies.

## Changes

The material in this document is for information only and is subject to change without notice. While reasonable efforts have been made in the preparation of this document to assure its accuracy, Odin TeleSystems Inc., assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.

Odin TeleSystems Inc. reserves the right to make changes in the product design without reservation and notification to its users.

## Warranties

THE PRODUCT AND ITS DOCUMENTATION ARE PROVIDED "AS IS" AND WITHOUT WARRANTY OF ANY KIND. ODIN TELESYSTEMS EXPRESSLY DISCLAIMS ALL THE WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. ODIN TELESYSTEMS DOES NOT WARRANT THAT THE FUNCTIONALITY OF THE PRODUCT WILL MEET ANY REQUIREMENTS, OR THAT THE OPERATIONS OF THE PRODUCT WILL BE UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS WILL BE CORRECTED. FURTHERMORE, ODIN TELESYSTEMS DOES NOT WARRANT OR MAKE ANY REPRESENTATIONS REGARDING THE USE OF THE PRODUCT OR ITS DOCUMENTATION IN TERMS OF THEIR CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE. NO ORAL OR WRITTEN INFORMATION OR ADVICE GIVEN BY ODIN TELESYSTEMS OR ODIN TELESYSTEMS' AUTHORIZED REPRESENTATIVE SHALL CREATE A WARRANTY. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO THE ABOVE EXCLUSION MAY NOT APPLY.

UNDER NO CIRCUMSTANCE SHALL ODIN TELESYSTEMS INC., ITS OFFICERS, EMPLOYEES, OR AGENTS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES (INCLUDING DAMAGES FOR LOSS OF BUSINESS, PROFITS, BUSINESS INTERRUPTION, LOSS OF BUSINESS INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT AND ITS DOCUMENTATION, EVEN IF ODIN TELESYSTEMS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN NO EVENT WILL ODIN TELESYSTEMS' LIABILITY FOR ANY REASON EXCEED THE ACTUAL PRICE PAID FOR THE PRODUCT AND ITS DOCUMENTATION. SOME JURISDICTIONS DO NOT ALLOW THE LIMITATION OR EXCLUSION OF LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY.



**Odin TeleSystems Inc.**  
<http://www.OdinTS.com>

This document is published by:

Odin TeleSystems Inc.  
P. O. Box 59686  
Dallas, Texas 75229  
U. S. A.

Printed in U. S. A.



## 1. Abstract

This document provides a technical description of Odin TeleSystems' Thor-8-PCI and Thor-8-PCIe adapter card. This presentation is targeted to systems integrators and application developers who are developing telecommunications systems and/or software applications using the Thor-8-PCI and Thor-8-PCIe platform. The purpose of this document is to provide the needed information about the hardware to allow software developers to efficiently integrate Thor-8-PCI and Thor-8-PCIe into their overall system under design.

For information on how to develop host applications utilizing the OTX Hardware Device Driver Application Programming Interface (API), please refer to the "*Programmer's Guide for OTX Hardware API*" document (Odin TeleSystems Inc. document number 1411-1-SAA-1006-1). For help on how to install the Thor-8-PCI and Thor-8-PCIe card and the OTX Device Driver Software, please refer to the "*Installation Guide for OTX PCI Adapters*" (Odin document number 1512-1-HCA-1001-1).

## 2. Table of Content

1.	Abstract.....	3
2.	Table of Content.....	3
3.	Introduction to Thor-8-PCI.....	4
4.	Specifications.....	4
5.	Supported Driver Devices.....	5
5.1	Physical Devices.....	5
5.2	Logical Devices .....	6
6.	System Architecture.....	6
6.1	External Interfaces .....	7
6.1.1	PCI Host Bus Interface .....	8
6.1.2	H.100 Computer Telephony Bus Interface .....	8
6.1.3	Centronics Network Interfaces .....	10
6.1.4	OTX ASM Interface .....	14
6.1.5	JTAG Interface.....	14
6.2	Data Architecture.....	14
6.3	Control Architecture .....	17
6.4	Clock Architecture.....	17
6.5	Logical Subsystems .....	19
6.5.1	Line Interface Subsystem .....	19
6.5.1.1	Line Configurations.....	19
6.5.1.2	Fault Monitoring.....	20
6.5.1.3	Loopbacks.....	20
6.5.2	Switching Subsystem.....	20
6.5.3	Codec Subsystem.....	21





### 3. Introduction to Thor-8-PCI and Thor-8-PCIE

Thor-8-PCI and Thor-8-PCIE is multi-purpose T1/E1 interface adapter. The Thor-8-PCI and Thor-8-PCIE card allows Personal Computers (PCs) and other systems with a PCI bus to be interfaced with T1/E1 links.

Thor-8-PCI and Thor-8-PCIE is a member of the Odin Telecom frameworkX (OTX) product family. Thor-8-PCI and Thor-8-PCIE is supported by the OTX device driver and by the OTX Hardware Application Programming Interface (API). Equipped with the appropriate OTX software modules, Thor-8-PCI and Thor-8-PCIE can be utilized in a variety of T1/E1, Integrated Services Digital Network (ISDN), Frame Relay, and Signaling System #7 (SS#7) applications.

The Thor-8-PCI and Thor-8-PCIE supports eight (8) T1 or E1 interfaces at the speeds of 1.544 Mbps and 2.048 Mbps, respectively. Throughout the document the T1/E1 interfaces are referred to as Line Interfaces (LIs). The same board supports both T1 and E1. The operation mode as well as the line terminating impedance of 75 ohms or 100 ohms are software switchable. The card also supports a high-impedance mode for monitoring. Consequently, the Thor-8-PCI and Thor-8-PCIE card can be used to terminate eight (8) T1/E1 links or to monitor four (4) links.


The Thor-8-PCI and Thor-8-PCIE provides H.100 Computer Telephony Bus. The H.100 bus comprises of thirty-two (32) 2, 4, or 8 Mbit/s Time-Division Multiplexed (TDM) highways for board-to-board communication. On the Thor-8-PCI and Thor-8-PCIE board the H.100 highways are connected to a non-blocking time-space switch. The time-space switch allows 256 time-slots to be switched between H.100 highways and the local highways. 1024 time-slots can be switched locally between on-board devices. The H.100 bus is backwards compatible with the MVIP bus and the SCBus.

The Thor-8-PCI and Thor-8-PCIE board also contains an OTX Application Specific Module (ASM) socket. The ASM interface can be used to add daughter boards providing additional resources. For example, Thor-8-PCI and Thor-8-PCIE can be augmented with Vidar-5x4-ASM providing 4 TI TMS320C548 Digital Signal Processors (DSPs). By loading and running different programs in these DSPs, the Thor-8-PCI and Thor-8-PCIE adapter can support a variety of different telecom functions, such as tone detection and generation, HDLC sending and receiving, voice encoding and decoding, etc.

Finally, Thor-8-PCI and Thor-8-PCIE contains four (4) codecs. The codecs perform Analog-to-Digital (A/D) and Digital-to-Analog (D/A) conversions. Both the A-law and the u-law are supported. The codecs can be switched to any time-slots on the board. Standard handsets can be connected to the codecs to provide phone functionality.

## 4. Specifications

Thor-8-PCI and Thor-8-PCIE is a full-length PCI board. The physical dimensions of Thor-8-PCI and Thor-8-PCIE are shown in Figure 1.



**Figure 1. Thor-8-PCI and Thor-8-PCIE Physical Dimensions (inches).**

The Thor-8-PCI and Thor-8-PCIE operates with +5.0 V supply voltage.

## 5. Supported Driver Devices

### 5.1 Physical Devices

The Thor-8-PCI and Thor-8-PCIE supports the following physical API driver devices:

**TABLE 1. OTX Physical Driver Devices supported by Thor-8-PCI and Thor-8-PCIE**

Host Device	Device Type	Max #	Description
0	<i>OTX_DEVICE_THOR_PCI</i>	1	Board Device
<i>OTX_DEVICE_THOR_PCI</i>	<i>OTX_DEVICE_LI_TIE1</i>	8	T1/E1 Line Interface Devices
<i>OTX_DEVICE_THOR_PCI</i>	<i>OTX_DEVICE_TSS</i>	1	Time-Space Switch



**TABLE 1. OTX Physical Driver Devices supported by Thor-8-PCI and Thor-8-PCIE**

Host Device	Device Type	Max #	Description
<i>OTX_DEVICE_THOR_PCI</i>	<i>OTX_DEVICE_CODEC</i>	4	Codec performing A/D and D/A conversions for analog front ends.
<i>OTX_DEVICE_THOR_PCI</i>	<i>OTX_DEVICE_VIDAR_5x_ASM</i>	1	Vidar-5x4-ASM Daughter Board (OPTIONAL)

## 5.2 Logical Devices

The Thor-8-PCI and Thor-8-PCIE supports the following logical API driver devices:

**TABLE 2. OTX Logical Driver Devices supported by Thor-8-PCI and Thor-8-PCIE**

Host Device	Device Type	Max #	Description
<i>OTX_DEVICE_LI_T1E1</i>	<i>OTX_LDEVICE_HDLC_SENDER</i>	1	Logical Device for sending HdLc Framing
<i>OTX_DEVICE_LI_T1E1</i>	<i>OTX_LDEVICE_HDLC_RECEIVER</i>	1	Logical Device for receiving HdLc framing.
<i>OTX_DEVICE_LI_T1E1</i>	<i>OTX_LDEVICE_CAS_T1E1_SENDE R_RECEIVER</i>	1	Logical Device for T1/E1 Channel Associated Signalling (CAS)

In addition, DSPs on an ASM board can be loaded with various program packages to provide support for a variety of Logical Devices types. For example, the Signal Processing Package One (OtxSpm1) for Vidar-5x4-ASM provides support for the following API logical devices:

- *OTX\_LDEVICE\_TONE\_CONST\_VAL\_GENERATOR*
- *OTX\_LDEVICE\_TONE\_EFFECTS\_GENERATOR*
- *OTX\_LDEVICE\_TONE\_SINEWAVE\_GENERATOR*
- *OTX\_LDEVICE\_TONE\_DTMF\_GENERATOR*
- *OTX\_LDEVICE\_TONE\_DTMF\_DIALER*
- *OTX\_LDEVICE\_TONE\_SILENCE\_DETECTOR*
- *OTX\_LDEVICE\_TONE\_DTMF\_DETECTOR*
- *OTX\_LDEVICE\_DATA\_CONVERTER*
- *OTX\_LDEVICE\_HDLC\_SENDER*
- *OTX\_LDEVICE\_HDLC\_RECEIVER*



---

For more information on the physical and logical driver devices, please refer to “*Programmer’s Guide for OTX Hardware API*” (Odin document # 1412-1-SAA-1006-1).

## 6. System Architecture

The overall system architecture can be best described and understood through different architectural views or aspects. This document explores the systems architecture from the following angles:

1. **External Interface View:** The external interface view describes the external interfaces of the adapter board, and how they are connected to the various internal devices and modules.
2. **Data Architecture View:** The data architecture view illustrates how the Time - Division Multiplexed (TDM) serial data is connected and transferred through the board.
3. **Control Architecture View:** The control architecture view describes how the internal devices and modules can be controlled by the host processor.
4. **Clock Architecture View:** The clock architecture view specifies what clocking and synchronization options are available, how clocking is derived, and how it distributed to the various devices.
5. **Logical Subsystem View:** The logical subsystem view describes the logical design subsystems in the system. Each subsystem can comprise hardware, firmware and driver or on-board processor software.

It is important to note that one device within the board can be involved in several of these views, each view describing how one aspect of the device interfaces with other devices.


### 6.1 External Interfaces

The Thor-8-PCI and Thor-8-PCIe contains the following external interfaces:

- PCI Host Bus
- H.100 Computer Telephony Bus
- Centronics Network Interface with
  - 8 T1/E1 Line Interfaces
  - 4 Analog Interfaces for Handsets
  - 1 External Synchronization Clock Input
- OTX ASM Socket
- JTAG Port for DSP Control



The external interfaces of the Thor-8-PCI and Thor-8-PCIe card are illustrated in Figure 2.



**Figure 2. Thor-8-PCI and Thor-8-PCIe External Interfaces.**

### 6.1.1 PCI Host Bus Interface

The interface between the Thor-8-PCI board and the Host Computer is the PCI (Peripheral Connection Interconnect) bus. The electrical characteristics comply to the PCI Standard, Revision 2.1. For more information on the PCI bus, please contact the PCI special interest group, PCI SIG, <http://www.pcisig.com>.

The interface between the Thor-8-PCIe board and the Host Computer is the PCIe r1.0a (single lane). A single lane card like Thor-8-PCIe can also be plugged into multi-lane PCIe slots.

### 6.1.2 H.100 Computer Telephony Bus Interface

Thor-8-PCI and Thor-8-PCIe supports the H.100 Computer Telephony Bus standard. The H.100 bus is a collection of time-division multiplexed (TDM) digital telephony highways designed to carry telephony traffic between extensions boards within one PC chassis. The H.100 bus supports 32 TDM highways. The highways can be operated at 2.048, 4.096, or 8.192 MBit/s carrying 32, 64, or 128 64 kbit/s time-slots,



respectively. Up to 20 boards can be connected to one H.100 bus. The maximum distance between boards is 7 inches.

Within the PC chassis the data streams are passed from card to card using a 60 pin ribbon cable and AMP 1-557089-2 connectors. The H.100 connector is a 60-finger edge connector on the upper right-hand side (Figure 2) of the board. The pin-out of the H.100 connector is listed in Table 3.

**TABLE 3. Thor-8-PCI and Thor-8-PCIe H.100 Pin Assignments**

Pin	Signal	Pin	Signal
1	Reserved	2	Power to active devices (CT_+5Vdc)
3	TDM Highway 31 (CT_D31)	4	TDM Highway 30 (CT_D30)
5	TDM Highway 29 (CT_D29)	6	TDM Highway 28 (CT_D28)
7	GND	8	TDM Highway 27 (CT_D27)
9	TDM Highway 26 (CT_D26)	10	TDM Highway 25 (CT_D25)
11	TDM Highway 24 (CT_D24)	12	GND
13	TDM Highway 23 (CT_D23)	14	TDM Highway 22 (CT_D22)
15	TDM Highway 21 (CT_D21)	16	TDM Highway 20 (CT_D20)
17	GND	18	TDM Highway 19 (CT_D19)
19	TDM Highway 18 (CT_D18)	20	TDM Highway 17 (CT_D17)
21	TDM Highway 16 (CT_D16)	22	GND
23	TDM Highway 15 (CT_D15)	24	TDM Highway 14 (CT_D14)
25	TDM Highway 13 (CT_D13)	26	TDM Highway 12 (CT_D12)
27	GND	28	TDM Highway 11 (CT_D11)
29	TDM Highway 10 (CT_D10)	30	TDM Highway 9 (CT_D9)
31	TDM Highway 8 (CT_D8)	32	GND
33	TDM Highway 7 (CT_D7)	34	TDM Highway 6 (CT_D6)
35	TDM Highway 5 (CT_D5)	36	TDM Highway 4 (CT_D4)
37	GND	38	TDM Highway 3 (CT_D3)
39	TDM Highway 2 (CT_D2)	40	TDM Highway 1 (CT_D1)
41	TDM Highway 0 (CT_D0)	42	GND
43	Frame Sync from "A" Clock Master (/CT_FRAME_A)	44	GND
45	Bit Clock from "A" Clock Master (CT_C8_A)	46	GND
47	Secondary Network Timing Reference (CT_NETREF)	48	GND
49	Redundant Frame Sync from "B" Clock Master (/CT_FRAME_B)	50	GND



**TABLE 3. Thor-8-PCI and Thor-8-PCIE H.100 Pin Assignments**

Pin	Signal	Pin	Signal
51	Redundant Bit Clock from “B” Clock Master (CT_C8_B)	52	GND
53	Message Channel (CT_MC)	54	GND
55	Compatibility Frame Pulse (/FR_COMP)	56	GND
57	SCbus System Clock (SCLK)	58	GND
59	SCbus System Clock time two (SCLKx2)	60	GND
61	MVIP-90 bit clock (C2)	62	GND
63	MVIP-90 bit clock time two (/C4)	64	GND
65	H-MVIP 16 Mhz Clock (/C16+)	66	H-MVIP 16 Mhz Clock /C16-
67	GND	68	RESERVED


For more information on the H.100 bus, please contact the Enterprise Computer Telephony Forum, ECTF, <http://www.ectf.org>.

### 6.1.3 Centronics Network Interfaces

The back panel of Thor-8-PCI and Thor-8-PCIE contains a Centronics connector with 50 contacts. The Centronics connector provides the following interfaces:


- 8 T1/E1 4-wire Line Interfaces
- 4 Analog Interfaces for Handsets
- 1 External Synchronization Clock Input

Thor-8-PCI and Thor-8-PCIE is delivered with a telco-type connector cable (SCSI Cable) and a Harmonica module which converts from Centronics connector to 12 RJ-11 connectors. The Harmonica module allows the connection of T1/E1 lines, handsets, and the external synchronization clock to Thor-8-PCI and Thor-8-PCIE using RJ-11 connectors (See Figure 3).



**Figure 3. Thor-8-PCI and Thor-8-PCle Harmonica Module**

Although Thor-8-PCI and Thor-8-PCle is delivered with the RJ-45 / RJ-11 Harmonica module, the modular structure of Thor-8-PCI and Thor-8-PCle allows it to be adapted for other types of connectors as well. For example, if the application requires BNC or Bantam type connectors, the Harmonica module can be replaced with another type of adapter which converts from Centronics to BNC or Bantam type connectors. The pin-outs of the Centronics and the RJ-11 connectors are documented in Figure 4 and in Table 4.



**Figure 4. Thor-8-PCI and Thor-8-PCle Centronics Connector.**



**TABLE 4. Thor-8-PCI and Thor-8-PCIE Centronics Connector Pin Assignments**

Pin	Signal	Pin	Signal
1	Codec-0, Speaker (+)	26	Codec-0, Speaker (-)
2	Codec-0, Handset Microphone (+)	27	Codec-0, Handset Microphone Ground
3	Codec-1, Speaker (+)	28	Codec-1, Speaker (-)
4	Codec-1, Handset Microphone (+)	29	Codec-1, Handset Microphone Ground
5	Codec-2, Speaker (+)	30	Codec-2, Speaker (-)
6	Codec-2, Handset Microphone (+)	31	Codec-2, Handset Microphone Ground
7	Codec-3, Speaker (+)	32	Codec-3, Speaker (-)
8	Codec-3, Handset Microphone (+)	33	Codec-3, Handset Microphone Ground
9	External Sync Clock In	34	Ground
10	Line Interface 0, Transmit Line (tip)	35	Line Interface 1, Transmit Line (ring)
11	Line Interface 0, Receive Line (tip)	36	Line Interface 1, Receive Line (ring)
12	Line Interface 1, Transmit Line (tip)	37	Line Interface 1, Transmit Line (ring)
13	Line Interface 1, Receive Line (tip)	38	Line Interface 1, Receive Line (ring)
14	Line Interface 2, Transmit Line (tip)	39	Line Interface 2, Transmit Line (ring)
15	Line Interface 2, Receive Line (tip)	40	Line Interface 2, Receive Line (ring)
16	Line Interface 3, Transmit Line (tip)	41	Line Interface 3, Transmit Line (ring)
17	Line Interface 3, Receive Line (tip)	42	Line Interface 3, Receive Line (ring)
18	Line Interface 4, Transmit Line (tip)	43	Line Interface 4, Transmit Line (ring)
19	Line Interface 4, Receive Line (tip)	44	Line Interface 4, Receive Line (ring)
20	Line Interface 5, Transmit Line (tip)	45	Line Interface 5, Transmit Line (ring)
21	Line Interface 5, Receive Line (tip)	46	Line Interface 5, Receive Line (ring)
22	Line Interface 6, Transmit Line (tip)	47	Line Interface 6, Transmit Line (ring)
23	Line Interface 6, Receive Line (tip)	48	Line Interface 6, Receive Line (ring)
24	Line Interface 7, Transmit Line (tip)	49	Line Interface 7, Transmit Line (ring)
25	Line Interface 7, Receive Line (tip)	50	Line Interface 7, Receive Line (ring)


There are two types of Thor-8-PCI and Thor-8-PCIE harmonicas:

- RJ-11 T1/E1 connectors (HMA-1062-1)
- RJ-45 T1/E1 connectors (HMA-1062-2)

The RJ-11 pin-outs in the HMA-1062-1 Harmonica module for the 4-wire T1/E1 line interfaces are shown in Figure 5.


**Figure 5. RJ-11 Connector for the T1 or E1 Interface (HMA-1062-1).**

The RJ-45 pin-outs in the HMA-1062-2 Harmonica module for the 4-wire T1/E1 line interfaces are shown in Figure 6.



**Figure 6. RJ-45 Connector for the T1 or E1 Interface (HMA-1062-2).**

The RJ-45 pin out for the handsets is shown in Figure 7.



**Figure 7. RJ-11 Connector for the Handsets.**

#### 6.1.4 OTX ASM Interface

The Thor-8-PCI and Thor-8-PCIE board contains an OTX ASM (Application Specific Module) Interface (Reference Designators BJ5 and BJ6). The ASM Interface can be used to attach a daughter board modules to the Thor-8-PCI and Thor-8-PCIE board. The ASM daughter boards can add functionality, such as DSP or HDLC resources.

### 6.1.5 JTAG Interface

The JTAG port (reference designator BJ3) are used for:


- Board Testing
- Programming of Complex Programmable Logical Devices (CPLDs)
- Connecting the DSP emulator board for DSP Software Development.

For more information on how to use the JTAG port and the DSP emulator, please refer to “*Programmer's Guide for OTX C55x DSP Software Development Kit*” Odin Document # 1412-1-SAA-1007-1.

### 6.2 Data Architecture

Internally, Thor-8-PCI and Thor-8-PCIE utilizes serial TDM (Time-Division Multiplexed) data streams for transfer of data or voice. The internal serial TDM data streams are called “Highways.” External interfaces are called spans.

The serial highways provide data paths between physical devices as shown in Figure 8. If the physical device connects to more than one highway, the device specific highway port number is also shown in Figure 8.



**Figure 8. Thor-8-PCI and Thor-8-PCIE Highway Connections.**



The Thor-8-PCI and Thor-8-PCIE internal highways are configured to operate at 2.048 Mbit/s or 8.196 Mbit/s, each containing 32 or 128 8-bit time-slots, respectively. The data rate of one time-slot is 64 kbit/s. Table 5 lists the internal highways used on Thor-8-PCI and Thor-8-PCIE boards.

**TABLE 5. Thor-8-PCI and Thor-8-PCIE Highway Connections**

Highway #	Connecting Time-Space Switch to
0	8.196 Mbits/s Highway connecting to LI#0, LI#1, LI#2, and LI#3
1-3	Reserved
4	8.196 Mbits/s Highway connecting to LI#4, LI#5, LI#6, and LI#7
5-9	Reserved
10-13	ASM Daughter Board
14	Quad Codec
15	Reserved

The time-space switch is non-blocking and allows any internal time-slot on any internal highway to be switched to any other highway/time-slot. The cross-connections are software programmable and automatically taken care of by the OTX driver.

In addition, the Thor-8-PCI and Thor-8-PCIE contains external several highways:

- 8 Highways mapped to the T1/E1 spans
- 32 H.100 Highways


The Thor-8-PCI and Thor-8-PCIE time-space also provides support multicasting and messaging. In multicasting mode any input channel can be cross-connected to multiple output channels. For example, an incoming LI time slot can be both switched to an outgoing H.100 Highway and it can also be switched to the Codec or ASM board.

In the messaging mode, the time-space switch can be instructed to send a constant byte on any time slot. Once activated, every byte on the specified time slot will contain the same value. The generation of constant byte does not consume any processing capacity. The constant byte feature is useful in, for example, verification of a through connection or in Bit Error Rate (BER) testing.



### 6.3 Control Architecture


The host PC can control the physical devices on the Thor-8-PCI and Thor-8-PCIE board through the PCI bus. The Thor-8-PCI and Thor-8-PCIE control architecture is illustrated in Figure 9.



**Figure 9. Thor-8-PCI and Thor-8-PCIE Control Architecture.**

### 6.4 Clock Architecture

On the Thor-8-PCI and Thor-8-PCIE board all the internal TDM data highways and the all the devices processing TDM data are synchronized to one clock reference. The clock reference can be derived from multiple sources and then switched to all the devices. The clocking sources supported by Thor-8-PCI and Thor-8-PCIE are illustrated in Figure 10 and listed in Table 6.



**Figure 10. Thor-8-PCI and Thor-8-PCIE Clock Architecture Overview.**

**TABLE 6. Thor-8-PCI and Thor-8-PCIE Clocking Sources.**

Clock Source	Description
A	8 kHz frame clock extracted from one of the incoming T1/E1 spans (0-7).
B	On-board free running oscillator.
C	External 8 kHz framing clock
D	H.100 Reference Clock

In the event that the clocking source is lost, Thor-8-PCI and Thor-8-PCIE will automatically switch to a backup clocking source. For example, if clocking is derived from an incoming T1/E1 span, and the span experiences Loss of Signal (LOS), the clocking source is automatically switched to the other T1/E1 span. If the other span loses signal as well, then Thor-2 will switch to free-running mode and the clocking will be derived from the on-board oscillator. If the H.100 clocks or the external clocks are used as the clocking source and the clocking is lost, Thor-8-PCI and Thor-8-PCIE will switch into free-running mode and use the on-board oscillator.

It is important to understand that the difference between the clocks on the external T1/E1 spans and the internal clocks. When the Thor-8-PCI and Thor-8-PCIE clocking is



derived from one incoming T1/E1 span, the external T1/E1 span and the internal highways on-board are completely synchronized. In that case, the other T1/E1 span is not necessarily in synchronization with the internal highways. To compensate for that, Thor-8-PCI and Thor-8-PCIE implements an elastic receive buffer with a size of 64x8 bits. The elastic store is used to adapt the clock rates between the T1/E1 clock and the Thor-8-PCI and Thor-8-PCIE system clock, to compensate for input wander and jitter, and to align the received frame with the internal highway frame. However, the elastic buffer may eventually over- or underflow and a slip condition may occur. When a positive or negative slip occurs, Thor-8-PCI and Thor-8-PCIE will discard one received layer-1 frame to free space in the elastic receive buffer and to continue forwarding the data from incoming T1/E1 span to the internal highway. The slip condition will cause a one 8-bit data sample to be discarded on all of the time-slots.

The occurrence of slips is normal in telephone network. A loss of data sample in a voice data is insignificant cannot be detected by human ear. Loss of one data byte in a data transmission is typically detected with Cyclic Redundancy Checks (CRC). A loss of a data byte due to a slip is typically corrected by the data link protocol requesting a retransmission of the corrupted packet.

## 6.5 Logical Subsystems

The logical subsystem view describes the logical design subsystems within the Thor-8-PCI and Thor-8-PCIE adapter. Each subsystem can comprise hardware, firmware, and driver or on-board processor software. The Thor-8-PCI and Thor-8-PCIE consists of two subsystems:

1. Line Interface Subsystem
2. Switching Subsystem
3. Codec Subsystem

### 6.5.1 Line Interface Subsystem

The Line Interface subsystem is responsible for interfacing the Thor-8-PCI and Thor-8-PCIE card with the external T1/E1 links. The subsystem provides the connectors, terminating resistors, transformers, and overvoltage protection.

#### 6.5.1.1 Line Configurations

The Thor-8-PCI and Thor-8-PCIE line interfaces support several different line codes:

- HDB3 - High Density Bipolar 3
- B8ZS - Bipolar 8 Zero Substitution
- AMI - Alternate Mark Inversion
- AMI with NZC



For the T1 operation mode, the following framing formats can be used:

- F4 - 4-frame multiframe
- F12 - 12 frame multiframe
- ESF - Extended Superframe
- F72 - 72 frame multiframe

For the E1 operation mode, Thor-8-PCI and Thor-8-PCIE supports the following framing formats:

- Doubleframe
- CRC multiframe

### 6.5.1.2 Fault Monitoring

The line interface subsystem supports fault and performance monitoring. The transceiver subsystem detects and reports the following alarms in the receive streams:

- Framing errors
- Cyclic Redundancy Check (CRC) errors
- Code violations
- Loss of frame alignment
- Loss of Signal (LOS)
- Alarm Indication Signal (AIS)
- E bit errors (E1 only)
- Slip
- Remote Alarm Indication (RAI, Yellow Alarm)

The line interface subsystems also supports the transmitting of the following alarms towards the remote end:

- Alarm Indication Signal (AIS)
- Remote Alarm Indication (RAI, Yellow alarm)
- Auxiliary Pattern (AUXP)

### 6.5.1.3 Loopbacks

The line interface subsystem implements a remote loopback for line testing. In the remote loopback mode, the clock and data recovered from the line inputs are routed back to the line outputs through the analog transmitter.



---

### 6.5.2 Switching Subsystem

The switching subsystem provides a time-space switch for the switching of any incoming time/slot to any outgoing time slot. This subsystem is also responsible for delivering and switching of the on-board clock signals. The switching subsystem has already been covered in Chapter 6.2: "Data Architecture" and Chapter 6.4: "Clock Architecture".

### 6.5.3 Codec Subsystem

The Thor-8-PCI and Thor-8-PCIE board contains four codecs allowing the user to listen in on any 4 internal time-slots. The codecs convert four digital Pulse Code Modulated (PCM) time-slots into analog electrical signals. The analog signals from the codecs can then be connected to standard telephone handsets through connectors 5 - 8 in the Harmonica.

The Thor-8-PCI and Thor-8-PCIE codecs support both A-law and u-law for the Analog-to-Digital and Digital-to-Analog conversions. The conversion law to be used can be selected by software.

Codec #0 is permanently connected to time-slot 1 (0 count) on the Internal Highway #14. Codecs 1 - 3 are connected to time-slots 2 - 4, respectively. The time-space switch can be used to cross-connect the codecs into any incoming or outgoing time-slot in the Line Interface, ASM, or H.100 Highways.

Doc. No. 1111-1-HAA-1019-1

For more information on this product, please contact:

Odin TeleSystems Inc.  
800 E. Campbell Road, Suite 334  
Richardson, Texas 75081  
U. S. A.

Tel: +1-972-664-0100  
Fax: +1-972-664-0855  
Email: [Info@OdinTS.com](mailto:Info@OdinTS.com)  
URL: <http://www.OdinTS.com/>

Copyright (C) Odin TeleSystems Inc., 1999-2012